## Proxima DP9210 Projector
## Technical and Functional Specifications

| | |
|---|---|
| **Computer Compatibility** | • SUN, SGI, IBM, HP, DEC, and X-Terminals graphics mode up to 135 MHz |
| | • IBM PC, PS/2, Pentium and compatibles |
| | • Apple Macintosh, Power Macintosh, and PowerBook families |
| **Video Compatibility** | • NTSC, NTSC 4.43, PAL, SECAM |
| **Sources** | • 2 computer |
| | • 2 video* |
| | • 1 S-video |
| **H-Sync Range** | • 15 to 81 KHz |
| **V-Sync Range** | • 50 to 100 Hz |
| **Brightness** | • 600 ANSI lumens |
| **Contrast Ratio** | • 250:1 (full on, full off) 100:1 (ANSI) |
| **Display Technology** | • 1.3" polysilicon active-matrix TFT (Thin Film Transistor) x 3 |
| **Resolution** | • XGA (1024 x 768) |
| **Resolutions Supported** | • VGA (640 x 480) |
| | • SVGA (800 x 600) |
| | • XGA (1024 x 768) |
| | • SXGA (1280 x 1024, scaled) |
| **Keystone Correction** | • 7° |
| **Number of Colors** | • 16.7 million |
| **Image Size (Diagonal)** | • 1.7 ft (0.5 m) to 53.3 ft (16.2 m) |
| **Lens** | • Motorized zoom lens 1.6:1 ratio |
| | • Focal length: 47mm to 75mm, f/2.5 to f/3.2 |
| **Projection Distance** | • 3.3 ft (1.0 m) to 92 ft (28.0 m) from screen |
| **Lamp** | • 120 watt UHP metal halide |
| | • Lamp life: 2,000 hours to 50% brightness |
| **Audio** | • Two 2-watt stereo speakers with 2-watt stereo speaker output jack (mini-jack) |
| **Remote Control** | • Includes zoom and focus control, and computer mouse control |
| **Approvals** | • FCC Class A, CE, UL, cUL |
| **Power Consumption** | • 200 watts |
| **Power Requirements** | • Auto switching 90 to 264 VAC, 50/60 Hz |
| **Operating Temperature (Sea Level)** | • 40° F (5° C) to 95° F (35° C) |
| **Weight** | • 14.1 lb (6.4 kg) |
| **Dimensions** | • 10.8 in. (W) x 15.6 in. (L) x 6.5 in. (H) |
| | • 27.5 cm (W) x 39.5 cm (L) x 16.6 cm (H) |
| **Warranty** | • Two years on parts and labor (excluding lamp) |

* Only 1 video input in some markets

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.